

Microwave Cavity Search for 0.1 meV Axions

P. L. Slocum, O. K. Baker, J. L. Hirshfield,
Y. Jiang, S. Kazakov, M. Lapointe, V. Yakovlev

Yale University

PATRAS Workshop


DESY

21 June, 2008



Overview

- “Light shining through walls” experiment: Simultaneous searches for
 - 0.1 meV axions
 - 0.1 meV hidden sector photons
- Status of experiment
- Plans for initial bench tests


Axion Searches




Photon-Paraphoton Oscillation



Limits on Photon-Paraphoton Mixing Parameter χ



34 GHz Microwave Source




- Output: 10 MW, 1us pulses at 10 Hz. Bandwidth=1 MHz.
- 500 kV, 215 A e- beam transverse deflection system:
 - Drive cavity (11.4 GHz), 3 gain cavities, and two final cavities.
 - Transverse beam momentum is transferred to RF fields at high efficiency.




O. A. Nezhevenko et al., IEEE Transactions on Plasma Science, 0093-3813/04, 2004.

Photos courtesy of M. Lapointe

Coaxial Cavities



Experiment



Expected Signal Power

For $g=2.5e-6/\text{GeV}$

$$\Pi_{\gamma \rightarrow \phi} \approx \frac{1}{4}(gBL)^2,$$

or $\Pi=10^{-15}$ for $B=8$ T and $L=10$ cm.

Probability Π^2 yields the expected signal power:

$$P_{LNB} = P_{beam} \Pi^2 Q_1 Q_2.$$

T(K)	Q_1	Q_2	P_{LNB}	N_{phot} at 34 GHz
300	1.5e4	2.e3	10^{-21} W	66 phot/s
40	9.e4	1.2e4	10^{-20} W	660 phot/s

Expected Noise Power

Friis' formula: $T_N = T_1 + \frac{T_2}{G_1} + \frac{T_3 - 1}{G_1 G_2} \dots$

$\Rightarrow T_N \approx 3(300\text{K}) + \frac{300\text{K}}{1000.} + \frac{300\text{K}}{1000.*10000.} + \dots \approx 900\text{K}.$

Assuming a flat thermal noise spectrum,


$$P_N = k_B T_N B = (1.38\text{e-}23 \text{ J/K})(900 \text{ K})(10^6 \text{ Hz}) = 10^{-14} \text{ W}$$

With gating ($\times 10^{-5}$), $P_N \sim 10^{-19} \text{ W}$, or **5300 photons/s** at 34 GHz.

From $\frac{N_s t}{\sqrt{N_B t}} \equiv 5$ where $N_s = 66 \text{ Hz}$ and $N_B = 5300 \text{ Hz}$,


$\Rightarrow t = 30 \text{ s}$ at $T = 300\text{K}$ (or 0.3 s at $T = 40\text{K}$).

5 σ Exclusion




*Cameron et al., Phys. Rev. D (47)9, 1993

5 σ Exclusion




* Jaeckel and Ringwald, Phys. Lett. B 659 (2008)

Cavity Q-factors



TEM₀₀₁




TE_{01n}

Using $\delta = \sqrt{2l/(\omega\sigma\mu)}$, with $\rho = \rho(T)$, and $\delta \rightarrow \delta(\omega\tau)^{1/2}$ for T=40K.

$$(\lambda/\delta_{300K} = 2.5e4; \lambda/\delta_{40K} = 1.4e5)$$


Cold Bore Cryostat




- Vacuum seal at both ends of bore.
- RF waveguides feed through vacuum seal.
- Cryostat can achieve 40K with 100W of heat dissipation.

Load Map for Single-Stage Cryocooler


RDK-400B Typical Load Map
Flex Line: 20M / Static Pressure 1.47MPa



Cut-off Frequencies for Cylindrical Cavity




Mode Chart for Cylindrical Cavity with $L = 5$ cm.



- 34.29 GHz
- TE011
- TE012
- TE013
- TE021
- TE022
- TE023
- TE031
- TE032
- TE033
- TE111
- TE112
- TE113
- TE121
- TE122
- TE123
- TE131
- TE132
- TE133
- TE211
- TE212
- TE213
- TE221
- TE222
- TE223
- TE231
- TE232
- TE233
- TE311
- TE312
- TE313
- TE321
- TE322
- TE323
- TE331
- TE332
- TE333


Q Factors for Cylindrical Cavity

Cylindrical Cavity: $Q\delta/\lambda$ vs. D/L




- TE011
- TE012
- TE013
- TE021
- TE022
- TE023
- TE031
- TE032
- TE033
- TE111
- TE112
- TE113
- TE121
- TE122
- TE123
- TE131
- TE132
- TE133
- TE211
- TE212
- TE213
- TE221
- TE222
- TE223
- TE231
- TE232
- TE233
- TE311
- TE312
- TE313
- TE321
- TE322
- TE323
- TE331
- TE332
- TE333


Microwave Source - Axial Layout



Preliminary Test



Expected Harmonics



Summary

- High-power 34 GHz microwave source at Yale provides a unique opportunity to search for particles with mass 0.1 meV.
- Design for resonant cavity, magnet, cooling system, and electronics are underway.
- Electronic components have been ordered from Miteq. Delivery expected in July 08 – initial tests with preliminary cavity will begin as soon as equipment arrives.